

Mobile Receipt & Label printer

XP-P103



Key features

- Easy paper loading
- 60s auto sleep and 60 mins auto off
- Optional interfaces choice
- Easy operate

Applications



Shopping



Mart



Restaurant



Hospital




Coffee Shop



Ticketing

XP-P103

Mobile receipt printer



Printing		XP-P103	
Printing method	Direct thermal		
Paper width	58mm		
Paper roll diameter	☒40mm		
Resolution	203 dpi		
Printing speed	70 mm/s		
Interface	USB+Bluetooth/ USB+WIFI/ USB+Bluetooth+WIFI		
Line spacing	3.75mm (changeable using commands)		
Character size	ANK, Font A:1.5×3.0mm(12×24 dots) Font B:1.1×2.1mm(9×17 dots) Chinese, traditional Chinese:3.0×3.0mm(24×24 dots)		
Column number	58mm paper: Font A - 32 columns/Font B - 42 columns/ Chinese, traditional Chinese - 16 columns		
Barcode Character			
Extented character sheet	PC347(Standard Europe) / Katakana/ PC850(Multilingual) / PC860(Portuguese) / PC863(Canadian-French)/ PC865(Nordic) / West Europe/ Greek/ Hebrew/ East Europe/ Iran/ WPC1252/Pc866(Cyrillic#2) / PC852(Latin2)/ PC858/ IranII/ Latvian/ Arabic/ PT151(1251)		
Barcode types	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128		
2D Barcode	QR CODE / PDF417		
Buffer			
Input buffer	32k bytes		
NV Flash	64k bytes		
Software			
Emulation	ESC/POS		
Driver	Windows/Linux/Android/Mac		
Utility	Windows & Linux test Utility		
SDK	iOS/Android/Windows		
Power			
Power adaptor	Input: AC 110V/240V, 50 ~ 60Hz		Output: DC 9V/2A
Printer power	DC 9V-2A		
Reliability			
Print head life	50 KM		
Physical characteristics			
Gross weight	0.215 kg		
Dimensions	107×76×50mm(D x W x H)		
Environmental Conditions			
Work environment	0 ~ 45℃, 10 ~ 80% RH		
Storage environment	-10 ~ 60℃, 10 ~ 90% RH (no condensation)		

